

VERAMAX PROOFING PAPER

EOB200 G13 Standard Semimatte Proofing Paper 200g Microporous Resin-Coated Paper

PRODUCT SPECIFICATIONS

| | | | |
|--------------|------------------------|------|---------|
| Finish | Satin | | |
| Caliper | 8.2 | mil | +/- 0.2 |
| Basis weight | 202 | gsm | +/- 6 |
| i1 Pro2 | L MO | 95.6 | |
| | a MO | 1.0 | |
| | b MO | -4.0 | |
| | L M1 | 95.6 | |
| | a M1 | 1.2 | |
| | b M1 | -5.3 | |
| Compliance | Gracol 2013 / Fogra 51 | | |
| OBA | Yes | | |

Printability

Frontlit only

Ink technology

A Aqueous inkjet

Compatibility

Most commercial thermal and piezo water-based printing systems from Canon, Epson and HP.

KEY APPLICATIONS

- Contract, design and dot proofs

PRODUCT AVAILABILITY

| Code | Dimension | Core size |
|--------------|------------|-----------|
| EOB200-17100 | 17" x 100' | 3" |
| EOB200-24100 | 24" x 100' | 3" |
| EOB200-42100 | 42" x 100' | 3" |

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.