

Laminates & Mounting Films

Overlamine Vinyl Films

General, everyday laminate with cold solvent acrylic pressure sensitive permanent adhesive. PVC base works well with almost any media type, unlike heat-assisted laminates.

KEY APPLICATIONS

Use with any film or smooth vinyl

COMPATIBILITY LEGEND

- A Aqueous Inks
- S Solvent Inks
- L Latex Inks
- U UV-Cured Inks

SPECIFICATIONS

	LAM3- GL or MT	LAM4- GL, ST or MT	LAM6-TEX	MAD3
Coating	na	na	na	na
Material	Clear vinyl	Clear vinyl	Clear vinyl	Clear vinyl
Face	Glossy or Matte	Glossy, Satin or Matte	Textured Matte	na
Caliper	3 mil	4 mil	6 mil	3.5 mil
Liner material	PE coated paper	PE coated paper	PE coated paper	PE/Paper
Liner weight	64 lb	64 lb	64 lb	50/150 lb
Adhesive	Acrylic PSA	Acrylic PSA	Acrylic PSA	Acrylic PSA/Silicon
Outdoor durability	3 years	1 year	1 year	na
Width(s)	38, 54, 60 in	38, 54, 61 in	38, 51, 61 in	38, 54 in
Length	164 ft	150 ft	150 ft	100 ft
Core	3 in	3 in	3 in	3 in
Compatibility	A L S U	A L S U	A L S U	A L S U

02-2018

Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. The ideal conditions for printing and storage are a temperature of 70-35°F and relative humidity of 33-50% RH.